



Radiator

**Rust Inhibitor & Conditioner
+Water Pump Lubricant**

Easy To Use

Add To Coolant Reservoir

PREVENTS

**Rust & Hose Degradation
UV Degradation
Cracking & Abrasion
Seal Degradation**

LUBRICATES & PRESERVES

**Water Pumps, Cooling
System, Hoses, Seals & More**

NET 8 FLUID OUNCES (237 ML)

**ZERO Oil Imports By 2025
www.aerohybridpower.com**

FOR PROFESSIONAL USE

For best results, this product should be applied by a qualified technician

CAUTIONS/WARNINGS

DO NOT APPLY to surfaces that create a hazard or require friction such as motor cycle seats, tire treads, brake rotors, drums, etc. **IF INGESTED** do not induce vomiting. If victim is conscious, give 2 glasses of water. Get medical attention.

EYE CONTACT Flush with water immediately & consult physician.

SKIN CONTACT Remove from skin, flush with water immediately, see a physician if irritation develops or persists.

IF INHALED Remove person to fresh air. If not breathing, give artificial respiration with barrier device. Get medical attention.

KEEP AWAY FROM CHILDREN & PETS

Aero Hybrid Power & Environmental
Systems, Hickory Hills, IL 60457

Part # 35-8-12



7 39957 35812 3

SAVE MONEY PREVENT BREAKDOWNS

DIRECTIONS

- Use as directed
- May be added to existing coolant or just after coolant has been flushed and replaced. We recommend a cooling system flush and new coolant for better results.
- 1 bottle added to radiator fluid reservoir every 15,000 to 20,000 miles improves anti-freeze protection, prevents rust, protects hoses and lubricates water pumps.

For additional application tips & directions go to:
aerohybridpower.com